

8550WLB†

# DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

Feature rich, offering ultimate garage protection.



## KEY FEATURES

### QUIETEST OPENER

in the LiftMaster®  
Lineup

### POWER-OUTAGE Performance

### WI-FI Built In

**BATTERY BACKUP**  
CALIFORNIA SB-969  
COMPLIANT

myQ Want to connect with other smart home gadgets?  
myQ® can do. [myQ.com](http://myQ.com)



## SECURE

**AUTOMATIC GARAGE DOOR LOCK CAPABLE:** DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

**TIMER-TO-CLOSE** CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

**SECURITY+ 2.0®** SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY myQ®.

**MOTION DETECTOR** LIGHTS THE WAY AUTOMATICALLY.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

## QUIET AND RELIABLE

**BELT DRIVE SYSTEM AND QUIET DC MOTOR** PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

**SOFT START/STOP** FOR SMOOTH OPERATION.

**INTEGRATED BATTERY BACKUP** ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

**WARRANTY** LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

## SMART

**BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**myQ MOBILE APP** LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

The State of California has not endorsed these or any other garage door openers. †8550W will transition to 8550WLB in mid 2019. \*Requires additional purchase of myQ Home Bridge 819LMB. \*\*Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. Smartphone not included. Application screens may vary. Cellular data or Wi-Fi connection required. Test equipment regularly and follow safety instructions.

## INCLUDED ACCESSORIES:

### SMART CONTROL PANEL®

LCD display enables simple programming and adjustment of settings.



880LMW

### 3-BUTTON REMOTE CONTROL

Operates up to 3 openers or myQ Light Accessories.



893MAX

### INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out.



485LM

## POWERFUL ADD-ONS:

### AUTOMATIC GARAGE DOOR LOCK CAPABLE

Deadbolts the garage door automatically every time it closes.



841LM

### REMOTE LIGHT CONTROL

Plug in any lamp to this device to control it with a smartphone or garage remote.



825LM

### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877MAX

PRODUCT GUIDE 8550WLB

DC BATTERY BACKUP BELT DRIVE  
WI-FI GARAGE DOOR OPENER

**LiftMaster®**

# MASTERFUL ENGINEERING.

8550WLB\*

DC BATTERY BACKUP BELT DRIVE  
WI-FI® GARAGE DOOR OPENER

## MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

## POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 6' Power Cord (3-Prong)

## MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)



## DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

9"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

# STANDARD SPECS.

## SECURITY

### SECURITY+ 2.0®

#### RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

#### 3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band\*\*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

\*\*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

#### ENCRYPTED CONTROLS

##### Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

## SMART

### myQ® RADIO

902-928 MHz  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.


### HOMELINK® COMPATIBLE

(VERSION 4.0 OR HIGHER\*\*\*)

\*\*\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

## ELECTRICAL

### LIGHTING



- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

# SHIPPING.

## SHIPPING WEIGHT

(in lbs.)

22  
HEAD

17  
RAIL

3  
AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

## CARTONS (3)

CARTON 1: 19.81" x 11.94" x 11.19"

- Garage Door Opener Head (8550WLB)
- Battery (485LM)

- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)

- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Belt T-Rail

CARTON 3 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LM)

## SAFETY AND SECURITY.

- Integrated Battery Backup
- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices



\*8550W will transition to 8550WLB in mid 2019.

†WARNING: to reduce the risk of injury to persons—

ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.

© 2019 The Chamberlain Group, Inc. All Rights Reserved.

LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc.

300 Windsor Drive, Oak Brook, IL 60523

LiftMaster.com

ALARM.COM is a registered service mark of Alarm.com. Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc. Google, Google Home, Google Assistant and other related marks and logos are trademarks of Google Inc. Nest is a trademark of Nest Labs, Inc. XFINITY Home and the XFINITY Home design logo are trademarks or service marks of Comcast Corporation. UL® and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation.

LMGDENPG8550WLB 2/19

**LiftMaster®**